

2017 FORD ESCAPE TECHNICAL SPECIFICATIONS

BODY			
Construction		Unitized welded steel body	
Final assembly location		Louisville Assembly Plant	
ENGINE			
Type	2.5-liter iVCT I-4	1.5-liter EcoBoost® I-4	Twin-scroll 2.0-liter EcoBoost I-4
Configuration	Aluminum block and aluminum head	Aluminum block and aluminum head	Aluminum block and aluminum head
Valvetrain	DOHC, four valves per cylinder	DOHC, four valves per cylinder	DOHC, four valves per cylinder
Bore x stroke	3.50 x 3.94 in.	3.11 x 3.20 in.	3.44 x 3.27 in.
Displacement	152 cu. in.	91.4 cu. in.	121 cu. in.
Compression ratio	9.7:1	10.0:1	9.3:1
Horsepower	168 @ 6,000 rpm	179 @ 6,000 rpm	245 @ 5,500 rpm*
Torque	170 @ 4,500 rpm	177 @ 2,500 rpm	275 @ 3,000 rpm*
Fuel	87 octane unleaded	87 octane unleaded	87 octane unleaded (min.)/91+ recommended
Fuel capacity	15.7 gallons	15.7 gallons	15.7 gallons
Fuel delivery	Sequential multiport injection	Direct injection	Direct injection
Fuel economy (City/Hwy/Combined)	21/28/24 (FWD)	23/30/26 (FWD) 22/28/24 (4WD)	22/29/25 (FWD) 20/27/23 (4WD)
Oil capacity	5.7 quarts with filter	5.7 quarts with filter	5.7 quarts with filter
Coolant capacity	9.2 quarts	6.9 quarts	6.9 quarts
DRIVETRAIN			
Layout	FWD	FWD/4WD	FWD/4WD
TRANSMISSION			
	Six-speed automatic with thumb switch	Six-speed automatic with paddle shifters	Six-speed automatic with paddle shifters
Gear ratios			
1st	4.58:1	4.58:1	4.58:1
2nd	2.96:1	2.96:1	2.96:1
3rd	1.91:1	1.91:1	1.91:1
4th	1.44:1	1.44:1	1.44:1
5th	1.00:1	1.00:1	1.00:1
6th	0.74:1	0.74:1	0.74:1
Reverse	2.94:1	2.94:1	2.94:1
Final drive			
	3.51:1, FWD	3.21:1, FWD; 3.51, 4WD	3.07:1, FWD/4WD
SUSPENSION			
Front	Independent MacPherson struts with 24-mm solid stabilizer bar (18-in. wheels), 25-mm hollow (17-in. and 19-in. wheels) stabilizer bar		
Rear	Control Blade™ with 18-mm solid (18-in. wheels), 19.5-mm solid (17-in. and 19-in. wheels) stabilizer bar		
STEERING			
Type	Rack-and-pinion with electric power-assist		
Ratio	15.2:1		
Turning circle, curb-to-curb	Right, 38 ft. 9.5 in.; left, 38 ft. 6.5 in.		
BRAKES			
Type	Standard four-channel, four-wheel discs with ABS and ESC		
Front	11.8-in. vented disc	12.6-in. vented disc	
Rear	11.0-in. solid disc	11.0-in. solid disc	
Power assist	Dual diaphragm		
WHEELS AND TIRES			
Base	17-in. steel with sparkle silver-painted covers, P235/55R17		
Largest	19-in. premium painted aluminum. P235/45R19		

*Tested using 93-octane fuel

2017 FORD ESCAPE TECHNICAL SPECIFICATIONS

DIMENSIONS (inches unless otherwise noted)			
Exterior			
Wheelbase	105.9		
Length	178.1		
Width, excluding mirrors	72.4		
Width, including mirrors	81.8		
Mirrors folded	75.0		
Vehicle height (without options)	66.3		
Minimum running ground clearance (FWD/4WD)	7.8		
Track, front, rear	61.5, 61.6		
Interior			
Seating capacity	Five		
Headroom			
First row	39.9		
Second row	39.0		
Legroom			
First row	43.1 (maximum)		
Second row	37.3		
Shoulder room			
First row	55.9		
Second row	55.2		
Hip room			
First row	54.5		
Second row	52.4		
WEIGHTS AND CAPACITIES			
SAE passenger volume total	98.7 cu. ft.		
Cargo volume	68.0 cu. ft. (behind first row) 34.0 cu. ft. (behind second row)		
Maximum towing capacity (properly equipped)	1,500 lbs.	2,000 lbs.	3,500 lbs.
Base curb weight	3,552 lbs., FWD	3,526 lbs., FWD 3,678 lbs., 4WD	3,613 lbs., FWD 3,765 lbs., 4WD

For editorial use only. Information correct at time of publication. Check media.ford.com for updates.