2017 FORD ESCAPE TECHNICAL SPECIFICATIONS

BODY				
Construction		Unitized welded steel body		
Final assembly location		Louisville Assembly Plant		
ENGINE		Louisville Assembly Flanc		
Type	2.5-liter iVCT I-4	1.5-liter EcoBoost® I-4	Twin-scroll 2.0-liter	
. , p =		1.5 11.61 LCODOO31 1 4	EcoBoost I-4	
Configuration	Aluminum block	Aluminum block	Aluminum block	
	and aluminum	and aluminum	and aluminum	
	head	head	head	
Valvetrain	DOHC, four valves per cylinder	DOHC, four valves per cylinder	DOHC, four valves per cylinder	
Bore x stroke	3.50 x 3.94 in.	3.11 x 3.20 in.	3.44 x 3.27 in.	
Displacement	152 cu. in.	91.4 cu. in.	121 cu. in.	
Compression ratio	9.7:1	9.99:1	9.7:1	
Fuel	87 octane unleaded	87 octane unleaded	87 octane unleaded	
			(min.)/91+	
			recommended	
Fuel capacity	16.2 gallons	16.2 gallons	16.2 gallons	
Fuel delivery	Sequential	Direct injection	Direct injection	
	multiport			
Oil capacity	injection 5.7 quarts	5.7 quarts	5.7 quarts	
Оп сарасіту	with filter	with filter	with filter	
Coolant capacity	9.2 quarts	6.9 quarts	6.9 quarts	
DRIVETRAIN	1 - 1 - 1	1 - 1 - 1 - 1	1	
Layout	FWD	FWD/4WD	FWD/4WD	
TRANSMISSION				
	Six-speed	Six-speed	Six-speed	
	automatic with	automatic with	automatic with	
Gear ratios	thumb switch	paddle shifters	paddle shifters	
1st	4.584:1	4.584:1	4.584:1	
2nd	2.964:1	2.964:1	2.964:1	
3rd	1.912:1	1.912:1	1.912:1	
4th	1.446:1	1.446:1	1.446:1	
5th	1.000:1	1.000:1	1.000:1	
6th	0.746:1	0.746:1	0.746:1	
Reverse	2.943:1	2.943:1	2.943:1	
Final drive	3.51:1, FWD	3.21:1, FWD;	3.07:1, FWD/4WD	
	3.31.1, FWD	3.51, 4WD	3.07.1, FWD/4WD	
SUSPENSION	l	3.31, 140		
Front	Independent MacPhersor	n struts with 24-mm solid sta	bilizer bar	
	(18-in. wheels), 25-mm	hollow (17-in. and 19-in. whe	eels) stabilizer bar	
Rear	Control Blade™ with 18-mm solid (18-in. wheels), 19.5-mm solid (17-in. and			
STEERING	19-in. wheels) stabilizer	bar		
	Dack and ninion with ale	octric nower assist		
Type Ratio	Rack-and-pinion with electric power-assist 15.2:1			
Turning circle,		Right, 38 ft. 9.5 in.; left, 38 ft. 6.5 in.		
curb-to-curb	1.4.5	, ==		
BRAKES				
Туре	Standard four-channel, four-wheel discs with ABS and ESC			
Front	11.8-in. vented disc	12.6-in. vented disc		
Rear		11.0-in. solid disc 11.0-in. solid disc		
Power assist	Dual diaphragm			
WHEELS AND TIRES				
Base	17-in. premium painted aluminum, P235/55R17			
Largest	19-in. premium painted aluminum, P235/45R19			

¹Tested using 93-octane fuel

2017 FORD ESCAPE TECHNICAL SPECIFICATIONS

DIMENSIONS (inches unless otherwise noted)					
Exterior					
Wheelbase	105.9				
Length	178.1				
Width, excluding mirrors	72.4				
Width, including mirrors	81.8				
Mirrors folded	75.0				
Vehicle height (without options)	66.3				
Minimum running ground clearance (FWD/4WD)	7.8				
Track, front, rear	61.5, 61.6				
Interior					
Seating capacity	Five				
Headroom					
First row	39.9				
Second row	39.0				
Legroom					
First row	43.1 (maximum)				
Second row	37.3				
Shoulder room					
First row	55.9				
Second row	55.2				
Hip room					
First row	54.5				
Second row	52.4				
WEIGHTS AND CAPACITIES					
SAE passenger	98.7 cu. ft.				
volume total					
Cargo volume	68.0 cu. ft. (behind first row) 34.0 cu. ft. (behind second row)				
Maximum towing capacity (properly equipped)	1,500 lbs.	2,000 lbs.	3,500 lbs.		
Base curb weight	3,552 lbs., FWD	3,526 lbs., FWD 3,678 lbs., 4WD	3,613 lbs., FWD 3,765 lbs., 4WD		

For editorial use only. Information correct at time of publication. Check <u>media.ford.com</u> for updates.